

**IN THE CLAIMS**

1. (currently amended) An intervertebral spacer device, comprising:

a spacer body dimensioned to fit between two vertebrae, the spacer body having a leading end, ~~and~~ a trailing end, and first and second sides extending between the leading and trailing ends;

the spacer body having a plurality of outer surfaces, the plurality of outer surfaces including an ~~convexly~~ curved upper surface extending between the leading end and the trailing end and the first and second sides of the spacer body and a ~~convexly~~ curved lower surface extending between the leading end and the trailing end and the first and second sides of the spacer body, the upper and lower surfaces facing away from one another, the upper and lower surfaces being convexly curved along a plane extending between the leading and trailing ends and along a plane extending between the first and second sides,

the spacer body having a plurality of linear grooves engagable by an intervertebral spacer device insertion tool having a plurality of linearly extending groove engagement members, the plurality of linear grooves including a first linear groove formed in the convexly curved upper surface and a second linear groove formed in the convexly curved lower surface, the first and second linear grooves being parallel to one another.

Claims 2 and 3 (canceled)

4. (original) The intervertebral spacer device of claim 1, wherein the spacer body has a rectangular pillow shape characterized by convex upper and lower surfaces and rounded corners and rounded edges.

5. (previously presented) The intervertebral spacer device of claim 1, wherein the plurality of linear grooves comprises a first pair of linear grooves formed in the upper surface and a second pair of linear grooves formed in the lower surface, the first pair of linear grooves being parallel to the second pair of linear grooves.

6. (previously presented) The intervertebral spacer device of claim 5, wherein each linear groove in the first pair of linear grooves is directly opposite a respective one of the linear grooves in the second pair of linear grooves.

7. (original) The intervertebral spacer device of claim 1, wherein the spacer body comprises a porous material.

8. (original) The intervertebral spacer device of claim 6, wherein the porous material of the spacer body is selected from the group consisting of porous metals, compacted wire meshes, bone morphogenic protein, and polylactic lactic acid.

9. (previously presented) The intervertebral spacer device of claim 1, wherein each of the first and second linear grooves has a rounded, smooth surface.

10. (original) The intervertebral spacer device of claim 8, wherein at least one of the first and second outer surfaces is rough.

Claims 11-19. (canceled)

20. (currently amended) An intervertebral spacer device comprising:

a spacer body dimensioned to fit between two vertebrae, the spacer body having a leading end and a trailing end and sides that extend between the leading and trailing ends;

the spacer body having a plurality of outer surfaces, the plurality of outer surfaces including a first outer surface and a second outer surface, the first and second outer surfaces facing away from one another, the first and second outer surfaces being convexly curved along a plane extending between the leading and trailing ends and along a plane extending between the sides,;

the spacer body having a plurality of linear grooves having a rounded surface that extends continuously between the leading and trailing ends of the spacer body, wherein the plurality of linear grooves includes at least one first linear groove formed in the first outer surface and at least one second linear groove formed in the second outer surface.

21. (previously presented) The intervertebral spacer device of claim 20, wherein the at least one first linear groove and the at least one second linear groove are parallel to one another.

Claim 22 (canceled)

23. (previously presented) The intervertebral spacer device of claim 20, wherein the at least one first linear groove includes a pair of first linear grooves formed in the first outer surface and extending between the leading and trailing ends of the spacer body.

Claims 24 and 25 (canceled)

26. (previously presented) The intervertebral spacer device of claim 20, wherein the at least one second linear groove includes a pair of second linear grooves formed in the second outer surface and extending between the leading and trailing ends of the spacer body.

Claims 27 and 28 (canceled)

29. (previously presented) The intervertebral spacer device of claim 20, wherein the at least one first linear groove comprises a first pair of linear grooves formed in the first outer surface and the at least one second linear groove comprises a second pair of linear grooves formed in the second outer surface, wherein the first pair of linear grooves are parallel to the second pair of linear grooves

30. (previously presented) The intervertebral spacer device of claim 29, wherein each of the linear grooves in the first pair of linear grooves is directly opposite a respective one of the linear grooves in the second pair of linear grooves.

Claims 31 and 32 (canceled)